

# Move/2500

Guarantee terminal availability whatever happens

- Assure terminal availability rate if power and network fail
- Make NFC payment a seamless consumer experience
- Robust and functional to meet merchants' daily needs





















The Move/2500 offers a seamless payment experience. A pocket-sized portable terminal, it complies with future security standards.

### Highest security

The Move/2500 is PCI-PTS 5.x certified. Its Telium TETRA OS uses the latest cryptographic schemes with future-proof key length.

### All payment options

The Move/2500 enables NFC couponing and wallet use cases, in addition to EMV Chip & PIN, swipe and contactlesss.

# Designed for mobility

Designed for indoor and outdoor use, the Move/2500 Portable is a pocket-size and offers extended battery. It is the perfect business companion for merchants.

# Guaranteed terminal availability

In a single terminal, the Move/2500 Hybrid comes with wired communication capabilities (Ethernet, PSTN) or wireless (3G, GPRS, Dual SIM) or WiFi. Then it guarantees terminal payment acceptance availability in case of network failures.

### Seamless NFC payment

The Move/2500 boosts contactless payment by offering customers a seamless experience through a dedicated card-reader zone and faster transaction flow.

## Secure Telium TETRA OS

Backed by 30 years of experience and with its user-friendly interface, the Telium TETRA operating system includes the best security mechanisms embedded to protect transaction privacy and leverages Ingenico's unique portfolio of payment applications.

# Eco-designed products

Ingenico Group adheres to a proactive eco-design policy. From design to production and market launch to recycling, we strive to minimize Ingenico's environmental footprint throughout product life cycles.









NAME			Move/2500 hybrid	Move/2500 portable
Processor	Application & Crypto processor	Cortex A5	•	•
Memory		128 MB RAM, 256 MB Flash 128 MB RAM, 512 MB Flash	Option	Option
OS	***************************************	Telium TETRA	•	•
SIM		2 SIM	Option	Option
SAM		2 SAM 3rd SAM	Option	Option
Card readers	Magstripe Smart card NFC/Contactless	ISO 1/2/3, 500K lifespan EMV Level 1, 500K lifespan EMV Level 1 compliant	•	•
Display	Colour	2.4" backlit , QVGA (320x240 pixels)	•	•
Keypad		16keys, raised marking, backlit 4 Functional Keys without backlight	•	•
Audio	Buzzer		•	•
Thermal Printer	Speed in lines/s Paper roll cage	Up to 24 lines/s 58 mm width x Ø 40mm	•	•
Terminal connectivity	WAN LAN	3G and/or GPRS WiFi	Option Option	Option
	Wired	Dial-up Modem RJ45 Ethernet 10/100 base T RJ45	•	X X
Terminal connections	USB Serial Power Supply	Micro USB Host & Slave RS 232 RJ11 Dedicated power jack	•	× ×
Battery	Li-ion	2200mAh	•	•
Terminal size	Portable Hybrid	168x81x58 mm (6.6x3.2x2.3") 168x81x69 mm (6.6x3.2x2.7")	•	•
Weight	Terminal + Battery	320 g (11 oz)	•	•
Environment	Operating Temperature Storage Temperature Operating Humidity	-10°C to +40°C (14°F to 104°F) -20°C to +55°C (-4°F to 131°F) 85% non-condensing at +40°C(104°F)	•	•
Security		PCI PTS 5.x & 4.x online & offline certified	•	•



